



TYPE SF/DF (SIMPLEX / DUPLEX FILTER)

Sizes	Capacity	Filtration
From 1/2" to 10"	Up to 2083 LPM	25 µm to 500 µm
Pressure	Viscosity	Mounting
Up to 21 Bar	Up to 10000 CST	Vertical



TYPE RNRV (NON RETURN VALVE)

Sizes	Types	Connection
From 1/2" to 12"	Non-Slame Type Swing Type Wafer Type	Between Flange Flanged Threaded



TYPE RBV (BUTTERFLY VALVE)

Sizes	Pressure	End Connection
From 2" to 12"	Up to 17 kg/cm2	Flanged, Wafer, Lug
Type of Butterfly Valve		
Zero Offset / Double Offset / Triple Offset		



TYPE RDIGI (INTERNAL GEAR PUMP)

Sizes	Capacity	Temperature
From 1/2" to 10"	Up to 390 M3/Hr	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 14 Bar	Up to 450000 CST	Foot



TYPE RLP (ROTARY LOBE PUMP)

Sizes	Capacity	Temperature
From 1" to 4"	Up to 3.55 Ltr/Rev	Up to 220 °C
Pressure	Viscosity	Mounting
Up to 7 Bar	Upt o 400000 CST	Foot



TYPE RDS (DOUBLE SCREW PUMP)

Sizes	Capacity	Temperature
Up to 14"	Up to 750 M3/Hr	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 25 Bar	Upt o 100000 CST	Foot & Flange



TYPE RTS (TRIPLE SCREW PUMP)

Sizes	Capacity	Temperature
Up to 6"	Up to 200 M3/Hr	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 25 Bar	Upt o 100000 CST	Foot & Flange



TYPE RPRV (PRESSURE RELIEF VALVE)

Sizes	Capacity	Temperature
Up to 1/2" to 3"	Up to 800 LPM	Up to 180 °C
Pressure	Viscosity	Mounting
Up to 30 Bar	Upt o 1000 CST	Foot & Flange (SAE)



ROTARY POSITIVE DISPLACEMENT PUMPS

A proven performer..



أرتك تریدینگ اند مینٹننس ذ.م.م
R TECH TRADING AND MAINTENANCE W.L.L
"Your partner in progress"
Official Partner in Qatar



**TYPE HGN (GENERAL PURPOSE GEAR PUMP)**

Sizes	Capacity	Temperature
From 1/2" to 3"	Up to 500 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 11 Bar	Up to 10000 CST	Foot

**TYPE HGBX (ROTARY GEAR SMALL OEMS PUMP)**

Sizes	Capacity	Temperature
From 1/4" to 2/2"	Up to 400 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 11 Bar	Up to 10000 CST	Flange & Foot

**TYPE HG SX (ALL STAINLESS STEEL ROTARY GEAR PUMP)**

Sizes	Capacity	Temperature
From 1/8" to 2 1/2"	Up to 350 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 11 Bar	Up to 10000 CST	Flange & Foot

**TYPE HGMX (ALL CAST STEEL ROTARY GEAR PUMP)**

Sizes	Capacity	Temperature
From 1/8" to 2 1/2"	Up to 350 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 11 Bar	Up to 10000 CST	Flange & Foot

**TYPE RDMNS/C (ALL SS/CS ROTARY GEAR PUMP)**

Sizes	Capacity	Temperature
From 3/4" to 6"	Up to 2050 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 11 Bar	Up to 100000 CST	Foot

**TYPE HG CX (MONOBLOCK ROTARY GEAR PUMP)**

Sizes	Capacity	Temperature
From 1/2" to 1"	Up to 60 LPM	Up to 150 °C
Pressure	Viscosity	Mounting
Up to 7 Bar	Up to 500 CST	Foot

**TYPE RDRN/RDRNF/RDRX/RDRXE/RDRB/RDRR (ROTARY TYPE TWIN GEAR PUMP)**

Sizes	Capacity	Temperature
From 1/2" to 6"	Up to 3333 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 11 Bar	Up to 100000 CST	Foot

**TYPE RDNX/RDBX (ROTARY HIGH PRESS. GEAR PUMP)**

Sizes	Capacity	Temperature
From 1/2" to 6"	Up to 3333 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 21 Bar	Up to 100000 CST	Foot & Flange

**TYPE RDNXF/RDBXF**

(ROTARY HIGH PRESS. GEAR PUMP) Vertical Design

Sizes	Capacity	Temperature
From 1/2" to 6"	Up to 3333 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 21 Bar	Up to 100000 CST	Flange

**TYPE RDRBJ/RDRNJ/RDRXJ (ROTARY JACKETED GEAR PUMP)**

Sizes	Capacity	Temperature
From 1/2" to 6"	Up to 3333 LPM	Up to 350 °C
Pressure	Viscosity	Mounting
Up to 11 Bar	Up to 100000 CST	Foot & Flange

**TYPE ET (ROTARY TRACODIAL PUMP)**

Sizes	Capacity	Temperature
From 1/2" to 1 1/4"	Up to 80 LPM	Up to 220 °C
Pressure	Viscosity	Mounting
Up to 11 Bar	Up to 1000 CST	Foot & Flange

**TYPE GTX (FUEL PRESSURISING GEAR PUMP)**

Sizes	Capacity	Temperature
From 3/8" to 3/4"	Up to 2500 LPH	Up to 220 °C
Pressure	Viscosity	Mounting
Up to 35 Bar	Up to 1000 CST	Foot & Flange

**TYPE SPN/SP-II (ROTARY GEAR PUMP)**

Sizes	Capacity	Temperature
From 1/2" to 2"	Up to 225 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 21 Bar	Up to 2500 CST	Foot

**TYPE GZ (ROTARY BARREL PUMP)**

Sizes	Capacity	Temperature
From 3/8" to 3/4"	Up to 750 Kg/Hr	Up to 110 °C
Pressure	Fluid	Mounting
Up to 30 Bar	Grease	Flexible

**TYPE NDX/NDNX (ROTARY TRIPLE TWIN BULK CARGO PUMP)**

Sizes	Capacity	Temperature
From 5" to 12"	Up to 550 M3/Hr	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 11 Bar	Up to 100000 CST	Foot

**TYPE FLS (FORCED LUBRICATION SYSTEM)**

Sizes	Capacity	Temperature
From 1/2" to 6"	Up to 2083 LPM	Up to 200 °C
Pressure	Viscosity	Mounting
Up to 21 Bar	Up to 100000 CST	Horizontal / Vertical

**TYPE DSK SKID (LOADING/UNLOADING SKIDS)**

Sizes	Capacity	Temperature
From 1/2" to 6"	Up to 2083 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 21 Bar	Up to 100000 CST	Horizontal / Vertical

**TYPE RDMS (ROTARY CHEMICAL ALL SS PUMP)**

Sizes	Capacity	Temperature
From 1/2" to 6"	Up to 2050 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 11 Bar	Up to 100000 CST	Foot

**TYPE RDZXI / RDZZXI / RDZZX (FIRE FIGHTING ROTARY GEAR PUMP)**

Sizes	Capacity	Temperature
From 1" to 6"	Up to 2082 LPM	Up to 250 °C
Pressure	Viscosity	Mounting
Up to 21 Bar	Up to 100000 CST	Foot & Flang

**PRESSURE PUMP (LOCOMOTIVE PRODUCT)**

Capacity	Pressure
1285 LPM	7 Kg/cm2
Application	Speed
Lube Oil	1270 RPM

**SCAVENING PUMP (LOCOMOTIVE PRODUCT)**

Capacity	Pressure
1710 LPM	7 Kg/cm2
Application	Speed
Lube Oil	1270 RPM

**WATER PUMP (LOCOMOTIVE PRODUCT)**

Capacity	Pressure
1710 LPM	3 Kg/cm2
Application	Speed
Water	2800 RPM

**GOVERNOR HOUSING (LOCOMOTIVE PRODUCT)**

Input Speed	Output Speed	Gear Ratio
1048 RPM	1048 RPM	1.0909

**LUBE OIL STRAINER (LOCOMOTIVE PRODUCT)**

Flow	Filtration	Pressure
Up to 3000 LPM	Up to 200 Microns	Up to 20 Bar